


XXPol 1710~2690MHzx2 65° 19.5dBi 2°~8° Integrated RCU (Remote Control Unit) Antenna.

Electrical specifications				
Frequency Range(MHz)	1710~2170 x2			
	1710~1990	1920~2200	2200~2490	2490~2690
Polarization	±45°			
Gain (dBi)	19.2±0.5	19.3±0.5	19.5±0.5	19.2±0.5
Horizontal 3dB beamwidth (°)	67±2.5	62±2.6	61±1.8	62±2.0
Vertical 3dB beamwidth (°)	5.0±0.4	4.4±0.3	4.1±0.3	3.9±0.3
Front-to-back ratio (dB)	>27	>27	>27	>27
Cross-polar ratio (dB)	>22 (0°)	>22 (0°)	>22 (0°)	>22 (0°)
Electrical downtilt (°)	2-8			
Sidelobe suppression (dB) (First sidelobe above main beam)	>17	>17	>16	>15
VSWR	<1.5			
Isolation: intra-system (dB)	>28			
Isolation: inter-system (dB)	>30			
Intermodulation IM3 (2x43dBm carrier)	≤-153dBc			
Impedance (Ω)	50			
Max. power per input (W) @50°C	250			
RET model	TRCU-TQ10P2V01(Replaceable, Included)			
RET protocol	AISG 2.0 SRET			
Lightning protection	DC Ground			

Mechanical specifications	
Connector	4x4.3-10-Female
Connector position	Bottom
Heightxwidthxdepth (mm)	1980x320x105
Packing size (mm)	2245x420x205
Antenna weight (kg)	19
Installation kit weight (kg)	5.4
Packing weight (kg)	28.8
Wind load (N,at 150km/h) Frontal/Lateral/Rearside	711/173/794
Max. wind velocity (km/h)	216
Radome material	Fiberglass
Radome color	Gray
Mechanical tilt (°)	0-10
Operating temperature (°C)	-50-65
Mounting hardware (mm)	Φ50-Φ115



1710-2690MHz

