



## MA-WC910-RHCP9

## 860-960 MHz Circular Polarization, RFID Reader Antenna

The RFID antenna from MARS is an innovative antenna that adds flexibility to the RFID system.

MA-WA910-RHCP9 antenna covers the standard 902-928 MHz RFID frequency, as well as a wide frequency band of 860-960 MHz with a RHCP circular polarization, low VSWR and axial ratio.

The antenna is designed for Point-to-Multipoint systems.

Additional features:

- · High efficiency.
- Superb co-siting performance due to low SSL and high F/B rejection.
- Unobtrusive, blends easily with the environment.
- Optionally available with Pole Mount or MNT-22 (pole/wall, azimuth and elevation adjustable mount).



## **Specifications**

| ectrical |
|----------|

| Frequency range                | 860 - 960 MHz      |
|--------------------------------|--------------------|
| GAIN, typ.                     | 9 dBic             |
| VSWR, max.                     | 1.7:1              |
| Polarization                   | RHCP               |
| 3 dB Beam-Width, H-Plane, typ. | 65°                |
| 3 dB Beam-Width, E-Plane, typ. | 65°                |
| Front to Back Ratio, typ.      | -20 dB             |
| Axial Ratio, typ.              | - 4 dB (5 dB max.) |
| Input power, max.              | 10 Watt            |
| Input Impedance                | 50 Ohm             |
| Lightning Protection           | DC Grounded        |

Mechanical

| Dimensions (HxWxD) | 305 x 305 x 30 mm (12" x 12" x 1.2")            |
|--------------------|---|
| Weight             | 0.5 kg.   |
| Connector          | N-Type, Female                                  |
| Back Plane         | Aluminum protected through chemical passivation |
| Radome             | UV Protected, Polycarbonate                     |
| Mount              | MNT-23  |

**Environmental** 

| -40°C to +65°C                            |
|---|
| According to IEC 60721-3-4                |
| 200 km/h (survival)                       |
| UL94                                      |
| IP-67                                     |
| ETS 300 019-1-4, EN 302 085 (annex A.1.1) |
| According to IEC 68-2-11                  |
| 25mm radial (survival)                    |
|   |

MARS Antennas & RF Systems proprietary information

MARS reserves the right to make technical changes or modifications to any of its products and specifications without prior notice and without implementing such changes to prior supplied products. Product images are representative and indicative only. Warranty terms and general conditions of sale are applicable on any purchase of any product, available on MARS website.

3 Hamanor st. Holon 5886103, P.O.Box 1852 Holon 5811801, Israel

Tel: +972-3-5599661 • Fax: +972-3-5599677 • e-mail: mars@marsant.co.il • web: www.mars-antennas.com