

MA-EG15-XX

GPS AVL Active Antenna

MARS GPS Active Antenna is exceptionally small sized and offers extremely wide coverage at low angles.

Additional Features:

- Reliable and stable performance.
- Dashboard or under dashboard mounting.
- Cable length with SMA connector option.
- Resists unfriendly environments.
- Built-in low noise amplifier.

Application:

- AVL, Automatic vehicular and asset location systems.
- GPS, time and location systems.

Cost effective solution for high volume deployment.



Specifications

Electrical

Frequency range	1575±1.24 MHz
GAIN, typ.	27 dBi
VSWR, max.	2 : 1
Polarization	Circular, RHCP
3 dB Beam-Width, H-Plane, typ.	Omni Directional
Noise Figure (Amp)	1.6 dB
Input power, max	30 mA / 3 V
Intercept Point	+10 dBm
Input Impedance	50 Ohm

Mechanical

Dimensions (HxWxD)	40 x 45 x 15 mm (1.6" x 1.8" x 0.6")
Weight	60 gr.
Connector	SMA, Male on a 1.8m RG 174 Cable
Radome	ABS

Environmental

Operating Temperature Range	-30°C to +60°C
Storage Temperature Range	-40°C to +70°C

Ordering Options

Mount Type	Replace X with
Magnetic	M
Glue	G
Fixed Mount	F
SMA, Male	A

MARS Antennas & RF Systems proprietary information

MARS reserves the right to make technical changes or modifications to any of its products and specifications without prior notice and without implementing such changes to prior supplied products. Product images are representative and indicative only. Warranty terms and general conditions of sale are applicable on any purchase of any product, available on MARS website.

3 Hamanor st. Holon 5886103, P.O.Box 1852 Holon 5811801, Israel

Tel: +972-3-5599661 • Fax: +972-3-5599677 • e-mail: mars@marsant.co.il • web: www.mars-antennas.com