

RADWIN D Plus Model

Point-to-Point Radio - Data Sheet (RW2000/ODU/DP/F58/FCC/EXT)



RW-2050-D200

Product Description

RW-2050-D200 is a carrier-class radio that belongs to the RADWIN 2000 D-Plus Series and supports 4.9 to 5.8 GHz frequency range.

The Radio complies with FCC/IC & FCC regulations with a factory default of 5.8 GHz FCC/IC.

RW-2050-D200 delivers up to 750 Mbps throughput.

The radio is connectorized for external antenna (2 x N-type).

Product Highlights

- 750 Mbps Ethernet net throughput
- Long range - Up to 120 km / 75 miles
- Telco-grade, extremely robust in harsh conditions
- Supports intra-site and inter-site synchronization to maximize capacity
- Configurable asymmetric throughput
- Advanced OFDM & MIMO technologies for operation in nLOS/NLOS and dense radio environments

Product Specifications:

Configuration					
Architecture	Outdoor Unit connectorized for external antenna (2 x N-type)				
PoE to ODU Interface	Outdoor CAT-5e; Maximum cable length: 100m for 10/100BaseT and 75m for 1000BaseT				
Radio					
Max Capacity	750 Mbps net aggregate throughput				
Range	Up to 120 km / 75 miles *				
Channel Bandwidth	Configurable: 10, 20, 40, 80 MHz (for the default band)				
Modulation	MIMO-OFDM (BPSK/QPSK/16QAM/64QAM/256QAM)				
Adaptive Modulation, Coding & Channel BW	Supported				
Automatic Channel Selection	Supported upon power up				
DFS	Supported (FCC, FCC/IC)				
Diversity	Supported				
Spectrum Viewer	Supported				
Max Tx Power	25 dBm per chain				
Duplex Technology	TDD				
Error Correction	FEC k = 1/2, 2/3, 3/4, 5/6				
Encryption	AES 128				
Support Indoor units	RADWIN PoE devices (RW-9921-101X)				
Uplink / Downlink Allocation	Configurable: Symmetric or Asymmetric				
QoS	Packet classification to 4 priority queues according to 802.1P or Diffserv				
VLAN Support	802.1Q, QinQ, 4094 VLANs				
TDD Intra Site Synchronization	Supported				
TDD Inter Site Synchronization	Supported through common GPS receiver per site				
Option 82	Supported				
RADIUS Authorization	Supported				
RADIUS User authentication	Supported				
Syslog	Supported				
Supported Bands					
Band	CBW 10MHz [GHz]	CBW 20MHz [GHz]	CBW 40MHz [GHz]	CBW 80MHz [GHz]	Radio Compliance
5.8 GHz FCC/IC (default)	5.730-5.845	5.730-5.845	5.730-5.845	5.730-5.845	FCC 47CFR Part 15.407; ISSED RSS-247
5.1 GHz FCC	5.170-5.250	5.170-5.250	5.170-5.250	5.170-5.250	FCC 47CFR Part 15.407
4.9 GHz FCC/IC	4.940-4.990	4.940-4.990	-	-	FCC 47CFR Part 90 Subpart Y; ISSED RSS-111
5.4 GHz FCC	-	5.480-5.715	5.480-5.715	5.485-5.715	FCC 47CFR Part 15.407
5.2 GHz FCC/IC	-	5.255-5.340	5.255-5.340	5.250-5.340	FCC 47CFR Part 15.407
Mechanical					
ODU Dimensions	28(w) x 19.5(h) x 8(d) cm				
ODU Weight	2.4 kg / 5.29 lbs				
Power					
Power Feeding	Power provided over ODU-IDU cable				
Power Consumption	<20W				
Environmental					
Operating Temperatures	-35°C to 60°C / -31°F to 140°F				
Humidity	100% condensing, IP67 (totally protected against dust and against immersion in water up to 1m)				
Safety					
US/CAN (cTUVus)	UL 60950-1, UL 60950-22, CAN/CSA C22.2 60950-1, CAN/CSA C22.2 60950-22				
CE/IEC	EN/IEC 60950-1, EN/IEC 60950-22				
EMC					
FCC	47 CFR, Part15, Subpart B, Class B				
ETSI	EN 300 386, EN 301 489-1, EN 301 489-4				
CAN/CSA-CFI/IEC	CISPR 22-2010 Class B				

Ordering Info

Part Number: RW-2050-D200

Description: RADWIN D Plus ODU, connectorized for external antenna (2 x N-type), supporting multi frequency bands at 5.x GHz, factory default 5.8 GHz FCC/IC.

* May be limited by regulation in the specific band being used

Datasheet information can be changed by manufacturer without prior notice

Corporate Headquarters, T. +972.3.766.2900, E. sales@radwin.com, www.radwin.com
HaBarzel St 27, Tel Aviv-Yafo, Israel

The RADWIN name is a registered trademark of RADWIN Ltd. © All rights reserved, March 2022
DS RW-2050-D200/3.22

RADWIN