



MA-CQ26-1X

380 MHz-6 GHz Multi Band Omni Antenna

MARS Multi Band Omni Antenna covers all the bands for 2G, 2.5G and 3G cellular, as well as ISM, WLAN, UNII, Bluetooth, Wi-Fi, WMTS and IMT-MC450. The antenna is aesthetic and has unobtrusive profile that blends easily with any environment.

The antenna is easy-installed and is highly recommended as an outstanding logistic solution for In-Building Installations.

The antenna is PIM certified, thus making it suitable for all multi-carrier systems.



Available in iBwave database

Specifications

_	lec		-	_
		·TP	-	21
	ŒL		•	o ı

Standard	TETRA, IMT- MC450, WMTS, DVB-T LTE	SMR, AMPS, CDMA, TDMA, GSM 900	WMTS, PCS, DECT, GSM 1900, UMTS	Bluetooth, ISM, WLAN	WLL, Broad- band access Licensed Band	Home land Security, UNII, WLL, H-LAN, Wi-Fi
Frequency range	380-806 MHz	806-960 MHz	1.395-1.432 1.71-2.17 GHz	2.3-2.5 GHz	3.3-3.7 GHz	4.9-6 GHz
GAIN, typ.	1 (2*)	4	5	5	5	6
VSWR, max.	3:1 (2.5:1*)	2:1	2:1	2:1	1.9 : 1	1.9 : 1
Polarization			Linear, Ve	rtical		
Input power, max.	50 Watt					
Input Impedance	50 Ohm					
PIM, 3rd order, 2X20W (option)	<-155 dBc					

Mechanical

Dimensions (HxWxD)	Base Diameter - 275 mm (10.8"), Height - 187 mm (7.36")
Weight	550 gr.
Connector	See Ordering Options
Back Plane	Aluminum; protected through chemical passivation
Radome	UV Protected Polycarbonate
Water Proofing	IP-67 (for outdoor use only)
Mount	Ceiling Mounting

Environmental

Operating Temp. Range	-40°C to +65°C
Vibration	According to IEC 60721-3-4
Flammability	UL94
Humidity	ETS 300 019-1-4, EN 302 085 (annex A.1.1)

Ordering Options

	•	
MA-CQ26-1X		Antenna Indoor
	MA-CQ26-1XT	Antenna Indoor with DC Return Option
	MA-CQ26-1XR	Antenna Outdoor
	MA-CQ26-1XDIN	Antenna Intdoor with 4.3-10 Female connector
	MA-CQ26-1XRDIN	Antenna Outdoor with 4.3-10 Female connector

^(*) Specifications for Ground Plate of 40 cm and up, or above a metal surface, with a spacing of 35-45 mm.

Patent Pending

Patterns are available on our website.

MARS Antennas & RF Systems proprietary information

MARS reserves the right to make technical changes or modifications to any of its products and specifications without prior notice and without implementing such changes to prior supplied products. Product images are representative and indicative only. Warranty terms and general conditions of sale are applicable on any purchase of any product, available on MARS website.

3 Hamanor st. Holon 5886103, P.O.Box 1852 Holon 5811801, Israel

Tel: +972-3-5599661 • Fax: +972-3-5599677 • e-mail: mars@marsant.co.il • web: www.mars-antennas.com