



MA-IS43-B2

433 MHz Base Station Panel Antenna

MARS 433 MHz Panel Antenna provides a cost effective solution for Pointto-Multipoint Systems based on the ISM 433 MHz.

- Additional Features:
 - Suited for new RFID technology applications. Excellent and stable performance.
 - Small and aesthetic profile.
 - UV protected antenna radome.
 - Suitable for both indoor and outdoor installations.
 - DC grounded.
 - Wall mount.



Specifications

	-	
 ^~t		,
 	rical	,

Frequency range	433±2 MHz
GAIN, min.	4 dBi
VSWR, max.	1.5 : 1
Polarization	Linear, Vertical
3 dB Beam-Width, H-Plane, typ.	95°
3 dB Beam-Width, E-Plane, typ.	100°
Side Lobes, min.	No Side Lobes
Cross Polarization, min.	No Cross Polarization
Front to Back Ratio, min.	No Front to Back Ratio
Input power, max.	25 Watt
Input Impedance	50 Ohm
Lightning Protection	DC Grounded

Mechanical

1 Toolium Cui			
Dimensions (HxWxD)	231 x 215 x 31 mm (9.1" x 8.5" x 1.2")		
Weight	840 gr.		
Connector	N-Type, Female		
Back Plane	Aluminum protected through chemical passivation		
Radome	UV Protected Polycarbonate		
Mount	Indoor Usage (Outdoor Version Available on Request)		

Environmental

Vibration According to IEC 60721-3-4 Wind Load 200 km/h (survival) Flammability UL94 Water Proofing IP-65 Humidity ETS 300 019-1-4, EN 302 085 (annex A.1.1) Salt Fog According to IEC 68-2-11 Ice and Snow 25mm radial (survival)	Operating Temperature Range	-40°C to +65°C
Flammability Water Proofing IP-65 Humidity ETS 300 019-1-4, EN 302 085 (annex A.1.1) Salt Fog According to IEC 68-2-11	Vibration	According to IEC 60721-3-4
Water Proofing IP-65 Humidity ETS 300 019-1-4, EN 302 085 (annex A.1.1) Salt Fog According to IEC 68-2-11	Wind Load	200 km/h (survival)
Humidity ETS 300 019-1-4, EN 302 085 (annex A.1.1) Salt Fog According to IEC 68-2-11	Flammability	UL94
Salt Fog According to IEC 68-2-11	Water Proofing	IP-65
<u> </u>	Humidity	ETS 300 019-1-4, EN 302 085 (annex A.1.1)
Ice and Snow 25mm radial (survival)	Salt Fog	According to IEC 68-2-11
	Ice and Snow	25mm radial (survival)

Ordering Options

MA-IS43-B2	N-Type Connector Version
MA-IS43-B21	N-Type + Cable RG58, ~25cm

Patterns are available on our website

MARS Antennas & RF Systems proprietary information

MARS reserves the right to make technical changes or modifications to any of its products and specifications without prior notice and without implementing such changes to prior supplied products. Product images are representative and indicative only. Warranty terms and general conditions of sale are applicable on any purchase of any product, available on MARS website.

3 Hamanor st. Holon 5886103, P.O.Box 1852 Holon 5811801, Israel

Fax: +972-3-5599677 • e-mail: mars@marsant.co.il • web: www.mars-antennas.com Tel: +972-3-5599661