

MA-WO25-9H

2.3 - 2.7 GHz Horizontal Omni Directional

MARS Horizontal polarized Omni Directional antenna provides coverage of 2.3-2.7 GHz with a stable and efficient performance of 10dBi gain.

MARS MA-WO25-9H provides a cost effective solution for large-scale applications and systems such as 802.11b/a. Point-to-multi-point, WLAN access points. WiMAX and more.

MARS Horizontal Omni Directional polarized antenna offers polarization rejection of interference of vertically polarized signals, as used in most WLAN systems.

Main Features:

- Horizontally polarized
- High gain.
- Lightweight and durable construction.
- UV protected radome suitable for harsh environment installations.



Specifications

	ical

Frequency range	2.3 - 2.7 GHz
GAIN, typ.	10 dBi
VSWR	2:1 max. 1.7:1 typ.
Polarization	Linear, Horizontal
3 dB Beam-Width Azimuth, typ.	Omni - Directional
3 dB Beam-Width Elevation, typ.	11°
Input power, max.	10 Watt
Input Impedance	50 Ohm
Lightning Protection	DC Grounded

Mechanical

· · · · · · · · · · · · · · · · · · ·		
Dimensions (L x Ø)	640 x 76 mm (25.2" x 3")	
Weight	750 gr.	
Connector	N-Type Female	
Radome	UV Protected Plastic	
Mount	2" Pole Mount	

Environmental

Operating Temp. Range	-40°C to +65°C
Vibration	According to IEC 60721-3-4
Flammability	UL94
Humidity	ETS 300 019-1-4, EN 302 085 (annex A.1.1)
Water Proofing	IP-65
Wind Load	200 km/h (survival)

Mars Antennas & RF Systems proprietary information

MARS reserves the right to make technical changes or modifications to any of its products and specifications without prior notice and without implementing such changes to prior supplied products. Product images are representative and indicative only. Warranty terms and general conditions of sale are applicable on any purchase of any product, available on MARS website.

3 Hamanor st. Holon 58861, P.O.Box 5 AZOR 58008, Israel

Fax: +972-3-5599677 • e-mail: mars@marsant.co.il • web: www.mars-antennas.com Tel: +972-3-5599661