



CommScope-Proprietary and Confidential. Preliminary specifications are for illustrative purposes only and will be updated prior to publication.

Low PIM Directional MIMO In-Building Antenna, 698–960 MHz, 1695–2700 MHz and 3300–4200MHz

Product Classification

Product Type In-building antenna

General Specifications

Application Indoor

Antenna Type Directional

Antenna Array Characteristic MIMO 2x2

Polarization ±45°

Color White (RAL 9016)

Number of Ports 2

Pigtail Cable 670-141SXE, plenum rated

Radome Material ASA+PC, UV stabilized

RF Connector Interface 4.3-10 Female

Dimensions

Width 199 mm | 7.835 in

Depth 80 mm | 3.15 in

Length 303 mm | 11.929 in

Pigtail Length 450 mm | 17.717 in

Electrical Specifications

Electrical Note Values typical, unless otherwise stated

Impedance 50 ohm

Operating Frequency Band 1695 – 2700 MHz | 3300 – 4200 MHz | 698 – 960 MHz

Electrical Specifications

Frequency Band, MHz	698–800	800–960	1695–2200	2200–2700	3300–4200
Gain, dBi	7.1	7.6	8.4	9	8
Beamwidth, Horizontal, degrees	77	77	70	60	54
Beamwidth, Vertical, degrees	71	68	62	56	64
Front-to-Back Ratio, Copolarization 180° ± 30°, dB	15	20	15	17	17
Isolation, Cross Polarization, dB	18	20	25	25	25
VSWR Return loss, dB	1.7 11.7	1.7 11.7	1.7 11.7	1.7 11.7	1.7 11.7
PIM, 3rd Order, 2 x 20 W, dBc	-153	-153	-153	-153	-153
Input Power per Port, maximum, watts	100	100	100	100	100

Environmental Specifications

Operating Temperature	-40 °C to +60 °C (-40 °F to +140 °F)
Relative Humidity	Up to 100%

Packaging and Weights

Width, packed	210 mm 8.268 in
Depth, packed	105 mm 4.134 in
Length, packed	350 mm 13.78 in
Included	Mounting bracket
Weight, gross	1.4 kg 3.086 lb
Weight, net	1.1 kg 2.425 lb

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant

