

13 dB, Tapper, 340 – 6000 MHz



**OBSOLETE**

This product was discontinued on: September 30, 2021

**Replaced By:**

CT-15-TUW-NI6      15 dB, Tapper, 340 – 6000 MHz

Product Classification

Regional Availability	Asia   Australia/New Zealand   EMEA   Latin America   North America
Product Type	Tapper

General Specifications

Device Type	Tapper
Application	Indoor/Outdoor
Color	White
Inner Contact Plating	Silver
Interface	N Female
Outer Contact Plating	Trimetal

Dimensions

Height	25 mm   0.984 in
Width	43 mm   1.693 in
Length	141 mm   5.551 in

Electrical Specifications

3rd Order IMD	-163 dBc
3rd Order IMD Test Method	Two +43 dBm carriers

# CT-13-TUW-NI6

<b>Insertion Loss at Frequency Band</b>	0.6 dB @ 1695–2700 MHz   0.6 dB @ 340–960 MHz   0.65 dB @ 3500–4500 MHz   0.65 dB @ 4900–6000 MHz
<b>Return Loss at Frequency Band</b>	19.1 dB @ 3500–4500 MHz   19.1 dB @ 4900–6000 MHz   20.8 dB @ 1695–2700 MHz   20.8 dB @ 340–960 MHz
<b>Average Power, maximum</b>	200 W
<b>Coupling</b>	13 dB
<b>Coupling Tolerance</b>	+0.25/-1.25dB @ 3500-4500 MHz   +0.3/-1dB @ 4900-6000 MHz   ±0.5dB @ 698-960 MHz   ±0.65dB @ 1695-2700 MHz   ±0.65dB @ 380-520 MHz   ±1.0dB @ 340-380 MHz
<b>Impedance</b>	50 ohm
<b>Operating Frequency Band</b>	1695 – 2700 MHz   340 – 960 MHz   3500 – 4500 MHz   4900 – 6000 MHz
<b>Peak Power, maximum</b>	3 kW
<b>Reflected Power, maximum</b>	200 W

## Mechanical Specifications

<b>Coupling Nut Proof Torque</b>	4.5 N-m   39.828 in lb
----------------------------------	------------------------

## Environmental Specifications

<b>Operating Temperature</b>	-35 °C to +85 °C (-31 °F to +185 °F)
<b>Relative Humidity</b>	Up to 100%
<b>Corrosion Test Method</b>	IEC 60068-2-11, 30 days
<b>Ingress Protection Test Method</b>	IEC 60529:2001, IP67

## Packaging and Weights

<b>Height, packed</b>	40 mm   1.575 in
<b>Width, packed</b>	90 mm   3.543 in
<b>Length, packed</b>	180 mm   7.087 in
<b>Weight, gross</b>	300 g   0.661 lb
<b>Weight, net</b>	250 g   0.551 lb

## Regulatory Compliance/Certifications

<b>Agency</b>	<b>Classification</b>
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on <a href="http://www.commscope.com/ProductCompliance">www.commscope.com/ProductCompliance</a>