

MA-WO7402700-5

740MHz - 2700MHz Multi Band Omni Directional Base Station Antenna

MARS Dual Band Base Station Antenna provides a cost effective solution for GSM 900/1800, LTE, WLL, WLAN, ISM, WiMAX, Point-to-Point and Point-to-Multi Point applications as well as MESH networks.

UV protected radome suitable for harsh environment installations. Antenna features stable and efficient performance with up to 6 dBi of gain.

Available in iBwave database



Specifications

Electrical

Frequency range	740-960 MHz	1710-2700 MHz
GAIN, typ.	4 dBi	6 dBi
VSWR,	1.5 : 1 (typ) 2 : 1 (max)	
Polarization	Linear, Vertical	
3 dB Beam-Width, H-Plane, typ.	Omni Directional	
3 dB Beam-Width, E-Plane, typ.	35°	
Input power, max	50 Watt	
Lightning Protection	DC Grounded	
Input Impedance	50 Ohm	

Mechanical

Dimensions (HxDia.)	470 x 66 mm (18.5" x 2.5")
Weight	350 gr.
Connector	N-Type, Female
Radome	UV Protected Plastic
Mount	2.5" PM (End) Attachment

Environmental

Operating Temperature Range	-40°C to +65°C
Vibration	According to IEC 60721-3-4
Wind Load	200 km/h (survival)
Flammability	UL94
Water Proofing	IP-67
Humidity	ETS 300 019-1-4, EN 302 085 (annex A.1.1)
Salt Fog	According to IEC 68-2-11
Ice and Snow	25mm radial (survival)

MARS Antennas & RF Systems proprietary information

MARS reserves the right to make technical changes or modifications to any of its products and specifications without prior notice and without implementing such changes to prior supplied products. Product images are representative and indicative only. Warranty terms and general conditions of sale are applicable on any purchase of any product, available on MARS website.

3 Hamanor st. Holon 5886103, P.O.Box 1852 Holon 5811801, Israel

Tel: +972-3-5599661 • Fax: +972-3-5599677 • e-mail: mars@marsant.co.il • web: www.mars-antennas.com