



Double Multi block hanger support systems are designed for organizing bundled runs of coax cable.

Each space-saving block securely holds two runs of coax, allowing a compact bundle of up to 6x runs to be supported by stacking three blocks.

FEATURES / BENEFITS

MBH114-6-F for illustration purpose

Technical features**GENERAL SPECIFICATIONS**

Product Line		Coaxial Cable Accessories
Product Type		Hanger
Hanger Type		Single Multi-block
Transmission Line Type		LCF158
Color		Black

MECHANICAL SPECIFICATIONS

Cable Size		1 5/8
Number of Cable / Waveguide Runs		2 per layer, 3 layers, 6 runs
Configuration		incl. Angle member adapter
Angle member adapter clamping range mm (in)		4 / 24 (0.157 / 0.945)
Angle member adapter threads		2x M8
Material		Metal parts: -Connecting devices:Stainless steel -Angle member adapter: Stainless steel -Plastic parts: Polypropylene
Length	mm (in)	330 (12.99)
Height	mm (in)	135 (5.31)
Width	mm (in)	55 (2.17)
Recommended / Maximum Clamp Spacing	m (ft)	1 / 1.2 (3.25 / 4)

TEMPERATURE SPECIFICATIONS

Operation Temperature	°C (°F)	-50 to 85 (-58 to 185)
Storage Temperature	°C (°F)	-50 to 85 (-58 to 185)

PACKAGING INFORMATION

Package Quantity		10
Weight per piece	kg (lb)	0.61 (1.35)
Weight per kit	kg (lb)	6.13 (13.5)
Box Dimensions (Bulk Shipping), L x W x H	mm (in)	480 x 340 x 185 (18.90 x 13.39 x 7.28)



MBH158-6-F

Double Multi-block hanger three layers, with angle member adapter



picture shows MBH114-6-F for illustration purpose

External Document Links

[Installation Instruction](#)

Notes