



Cell-Max™ Low PIM Omni In-building Antenna, 698–960 MHz, 1695–2700 MHz and 3300–4200 MHz 4.3-10. Not Recommended for metal ceilings.

Product Classification

Product Type	In-building antenna
Product Brand	Cell-Max™

General Specifications

Application	Indoor
Antenna Type	Omni
Antenna Array Characteristic	SISO
Polarization	Horizontal
Color	White
Mounting	Thru-hole ceiling mount (optional)
Mounting Note	For antenna installation on metal ceilings, please contact your local CommScope representative
Number of Ports	1
Pigtail Cable	670-141SX, plenum rated
Radome Material	ASA+PC, UV stabilized
RF Connector Interface	4.3-10 Female

Dimensions

Height	18 mm 0.709 in
Pigtail Length	400 mm 15.748 in
Outer Diameter	308 mm 12.126 in

Electrical Specifications

Electrical Note	Values typical, unless otherwise stated
Impedance	50 ohm

Operating Frequency Band 1695 – 2700 MHz | 3300 – 4200 MHz | 698 – 960 MHz

Electrical Specifications

Frequency Band, MHz	698–800	800–960	1695–2180	2200–2700	3300–4200
Gain, dBi	1.5	2.2	3.5	3.7	4
Beamwidth, Horizontal, degrees	360	360	360	360	360
VSWR Return loss, dB	1.6 12.7	1.6 12.7	1.6 12.7	1.6 12.7	1.6 12.7
PIM, 3rd Order, 2 x 20 W, dBc	-153	-153	-153	-153	-153
Input Power per Port, maximum, watts	50	50	50	50	50

Environmental Specifications

Operating Temperature -40 °C to +60 °C (-40 °F to +140 °F)
Relative Humidity Up to 100%

Packaging and Weights

Width, packed 320 mm | 12.598 in
Depth, packed 110 mm | 4.331 in
Length, packed 330 mm | 12.992 in
Packaging quantity 1
Weight, gross 1.1 kg | 2.425 lb
Weight, net 0.8 kg | 1.764 lb

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
ROHS	Compliant

