



MA-WOLTE-3X

Specifications

698 MHz-6.5 GHz Multi Band Omni Antenna

MARS Multi Band Omni Antenna covers all the bands for 2G, 2.5G and 3G cellular, as well as UHF (760-960 MHz), LTE (698-806 MHz), ISM, WLAN, UNII, Bluetooth and Wi-Fi bands.

The antenna is aesthetic, small and has unobtrusive profile that blends easily with any environment.

The antenna is easy-installed and is highly recommended as an outstanding logistic solution for In-Building Installations.

The antenna is PIM certified, thus making it suitable for all multi-carrier systems.

Available in iBwave database

Specifications									
			Electrical						
Standard		LTE	SMR, AMPS, CDMA, TDMA, GSM 900	PCS, DECT, GSM 1900, UMTS	Bluetooth, ISM, WLAN	WLL	UNII, WLL, H-LAN, Wi-Fi		
Frequency range		698-806 MHz	806-960 MHz	1.71-2.17 GHz	2.3-2.7 GHz	3.3-3.8 GHz	4.9-6.5 GHz		
GAIN, typ.		2	2	3-4	5	4	6		
VSWR, max.		2:1	2.2 : 1	1.9 : 1	2.1 : 1	2:1	2: 1		
Polarization		Linear, Vertical							
Input power, max.		50 Watt							
Input Impedance		50 Ohm							
PIM, 3rd order, 2X20W (option)		-150 dBc							
			Mechanical						
Dimensions (HxWxD)		Base Diameter - 205 mm (8.07"), Height - 89 mm (3.5")							
Weight		220 gr.							
Connector		N-Type, Female (See Ordering Options)							
Back Plane		Glass epoxy							
Radome		UV Protected Polycarbonate							
Mount	See Ordering Options								
			nvironment.	al					
Operating Temperature Range		-40°C to +65°C							
Vibration		According to IEC 60721-3-4							
Flammability		UL94							
Humidity		ETS 300 019-1-4, EN 302 085 (annex A.1.1)							
Ordering Options									
MA-WOLTE-3X	Ceiling Mountable								
MA-WOLTE-3X1	Ceiling option with central connector mounting (Long N-type 45 mm)								
MA-WOLTE-3XA	Ceiling Mountable with 38 cm pigtail								
MA-WOLTE-3XB	Ceiling/Wall Adjustable with MNT-22 mount								
MA-WOLTE-3XT	Ceiling/Wall Provision for Adjustable with MNT-22 mount with DC Return								
MA-WOLTE-3XP	Ceiling Mountable PIM certified								
MA-WOLTE-3X1P	Ceiling option with central connector mounting (Long N-type 45 mm) PIM certified					ed			
MA-WOLTE-3XAP	Ceiling Mountable with 38 cm pigtail PIM certified								
		Adjustable with MNT-22 mount PIM certified							
MA-WOLTE-3XTP	<u> </u>	l Provision fo	Provision for Adjustable with MNT-22 mount with DC Return PIM certified						
Patterns are available on c	our website								

Patent Pending

MARS Antennas & RF Systems proprietary information MARS reserves the right to make technical changes or modifications to any of its products and specifications without prior notice and without implementing such changes to prior supplied products. Product images are representative and indicative only. Warranty terms and general conditions of sale are applicable on any purchase of any product, available on MARS website.

3 Hamanor st. Holon 5886103, P.O.Box 1852 Holon 5811801, Israel								
Tel: +972-3-5599661	• Fax: +972-3-5599677 • e-mail: mars@marsant.co.il • web: www.mars-antennas.com							

