

### UHF Slim Omnidirectional Ceiling Mounting Antenna, 380-520 MHz, 3dBi

#### Operating Frequency Range

- 380-400 MHz, 400-450 MHz, 450-520 MHz

#### Features and Benefits:

- Indoor Ceiling-Mount Omnidirectional Antenna
- Low return loss, stable performance
- Ultra Low Profile, lightweight and easy to install
- Pigtail with 4.3-10 female or N-female
- Mounts directly and easily to ceiling tile



#### Technical & Mechanical Specifications

Electrical Specifications	
Frequency Range	380-400/400-450/450-520
Polarization	Vertical
Gain	2.0/2.5/3.0dBi
Horizontal Beamwidth	360°
Vertical Beamwidth	95°/75°/60
VSWR	<1.6
Maximum Input Power	50 W

Mechanical Specifications	
Connector Type	1 Port, 4.3-10 Female or N-Type Female
Mounting Type	fasteners and screws included for wall mounting
Dimensions	Φ 280*15 mm
Weight	0.5 kg
Radome Material	ABS
Radome Color	White

Ordering Options	
AO-3852V2360-43	Antenna with 12" Coaxial Plenum Rated Pigtail with 4.3-10 Female Connector
AO-3852V2360-N	Antenna with 12" Coaxial Plenum Rated Pigtail with N-Type Female Connector

**Note:** The antenna please not to install on the big area metals, in order to prevent influence antenna result.